



The workhorse that's also a sprinter

This Tank-Tough® printer offers flexible forms handling and lightning-fast throughput.

Highlights:

- Letter-quality 24-pin printer
- Zero-tear capability (through any paper path) with auto-advance
- Up to 610 characters-per-second print speed
- Crisp, clear printing—even on 5-part forms
- Rated at up to 8,000-hour MTBF
- Co-resident Epson®, IBM® and MICROLINE® emulations
- Networkable via optional Ethernet external print server
- Eight resident scalable barcodes and four text fonts
- ML395C prints in color via user-installable ribbon
- 1-Year limited Depot warranty, including parts, labor and printhead¹
- Live, toll-free technical support 24/7/365¹

The black-only OKI® MICROLINE® 395/four-color MICROLINE 395C printer delivers trouble-free reliability—with swift printing speeds, high-volume output, and flexible paper handling.

Each of its four print speeds is among the fastest in its class:

- At 610 cps, the High-Speed Draft mode blasts through spreadsheet reports in no time;
- The 485-cps Utility and 245-cps Near Letter Quality modes kick out drafts and memos at a rapid clip; and
- The 165-cps Letter Quality mode delivers crisp, clear correspondence and proposals in short order.

The ML395/ML395C is built Tank-Tough: it comes with a printhead rated for 200 million characters, and has an MTBF of 8,000 hours.

Multiple paper paths for added flexibility.

Use the ML395/ML395C's optional bottom push tractor and the bottom feed's straight-through paper path for those hard-to-handle labels, card stock, and forms with up to 5 parts. Add the top feed for single sheets and envelopes, the rear push feed for fanfold paper.

A time-saving "paper park" function lets you switch forms at the push of a button.

The printer even saves paper: its zero-tear function advances a printed page to the perforation and lets you tear sheets off cleanly and precisely. Then it positions the next page for printing—automatically.

Getting the job done — with style.

Make a lasting, professional-looking impression with the ML395/ML395C's four letter-quality resident fonts and eight resident barcode fonts.

With the ML395C, your graphics, charts, transparencies and text presentations will sizzle in a vibrant rainbow of colors, as well as black.

The ML395/ML395C lets you get up and running easily. It features parallel and serial interfaces for quick attachment to a variety of systems.

Rugged. Dependable. Virtually unstoppable. The ML395/ML395C is all that and more. Ask for the fast, flexible 24-pin workhorse that's sure to be a winner in your busy office: the ML395/ML395C.

¹ Available in the U.S. and Canada only.

MICROLINE® 395/395C

Specifications

Technology, Speed and Print Characteristics

- **Printhead:** 24-pin, (0.20 mm diameter)
- **Graphics Resolution:** 60 x 60 dpi (min.); 360 x 360 dpi (max.)
- **Feed Rate:** 10 ips
- **Print Speed and Character Matrix:**

Mode	LQ	NLQ	Utility	HS Draft
Speed (in cps)	165	245	485	610

Emulation, Interface and Memory

- **Emulation:** Epson® LQ 2550, IBM® XL24E AGM and IBM ProPrinter® co-resident
- **Interface:** Standard: Parallel and RS232-C Serial; Optional: OkiLAN® 10/100 Base-T External Print Server
- **Memory:** 64K RAM
- **Interface Buffer:** Max. 23K

Compatibility

- **Operating Systems:** Windows® 8x; Windows 7, Windows VISTA®, Windows XP, Windows Server 2012

Paper Handling

- **Paper Input:** Multi-Part Form, Continuous Form (non-overlap type), Cut Sheet, Card Stock, Envelopes (single feed)
- **Number of Copies:** Original plus 3
- **Single Sheet Thickness:** 0.002" to .0049" (0.05mm to 0.12mm)
- **Multipart Thickness:** Rear Feed: .014" (0.36mm); Bottom Feed: .02" (0.5mm)

- **Paper Weight:** Single Part – 12 to 24 lb.; Card Stock – 100 lb. or less
- **Paper Feeding:** Bottom, Top and Rear
- **Standard:** Built-in Push Tractor (Rear Feed), Friction Feed (Top)
- **Options:** Pull Tractor, Bottom Feed Push Tractor

Warranty and Reliability

- **Warranty:** 1-Year limited Carry-In Depot; parts, labor and printhead¹
- **MBTF:** 8,000 hours (25% duty/35% page density)
- **Monthly Workload:** 17,000 pages at 25% duty cycle/-35% density
- **Printhead Life:** 200 Million characters avg. at 25% duty cycle
- **Ribbon Life:** Black Ribbons – 5 million-character life; Color Ribbons – 7,800K-character life (all bands)

Environmental

- **Size (WxDxH):** 22.4" x 16.4" x 7.1" (57 cm x 41.7 cm x 18.0 cm)
- **Net Weight:** 37 lb. (17 kg); UPS shippable
- **Power Consumption:** 180 VA (max.) operating; 60 VA idle
- **Electrical:** 120V, 220/240V (+10%, -15%)
- **Frequency:** 50/60 Hz (±2%)
- **Operating Temperature:** 41° F to 104° F (5° C to 40° C) @ 20% to 80% relative humidity
- **Acoustic Noise:** 58dBA LQ mode; 56dBA Quiet mode

Ordering Information

Description	Part Numbers
MICROLINE 395-120V	62410501
MICROLINE 395-220/240V	62410502
MICROLINE 395C-120V	62410601
MICROLINE 395C-220/240V	62410602

Accessories

Pull Tractor Kit (with acoustic cover)	70011701
Bottom Feed Push Tractor Kit	70021601
OkiLAN® 6020e+ 10/100 Base-T Ethernet External Print Server	70036002

Ribbons:

Black Cartridge	52103601
Color Cartridge	52103701

OKIcare® Depot Warranty Extensions¹

	U.S.	Canada
ML395/ML395C 2-Year Depot	58251301	58251311
ML395/ML395C 3-Year Depot	58251401	58251411

OKIcare On-Site Warranty Extensions¹

	U.S.	Canada
ML395/ML395C 2-Year On-Site	58252301	58252311
ML395/ML395C 3-Year On-Site	58252401	58252411

For more information on Impact printers and supplies from OKI, including OKIcare® Extended Service Programs: **1.800.OKI.DATA** (800.654.3282).¹

¹ Available in the U.S. and Canada only.

Specifications are subject to change without notice.

Featured product may not be available in all countries. Please contact your local office for regional availability.

© 2015 Oki Data Americas, Inc. OKI, MICROLINE, OkiLAN, OKIcare Reg. T.M., Oki Electric Industry Co., Ltd. 7-Day/24-Hour logo T.M., Oki Data Americas, Inc. Epson Reg. T.M., Seiko Epson Corp. IBM, ProPrinter Reg. T.M., International Business Machines Corp. Windows Vista, Reg. T.M., Microsoft Corp.

SELLCOM

Authorized Okidata from www.sellcom.com/okidata.html
800SELLCOM 919-401-0067 support@sellcom.com

